



REV	CONTENT	CHK	DATE
V0.0	CONTENT	CXL	20.05.11
V0.1	更改建议PCB板焊接孔尺寸	CXL	21.01.13
V0.2	修正图面	CXL	22.04.01
V0.3	修正图面	CXL	22.12.01

Electrical :

	UL	IEC
1.Rated Voltage :	300V	320V
2.Rated Current :	12A	17.5A
3.Wire Range:	28-14AWG	0.2-1.5mm ²
4.Stripping Length :	8-9mm	
5.Withstanding Voltage :	AC1600V/1Min.	
6.Operating Temperature :	-40°C~+130°C	
7.RoHS Compliance		
8.Safty Approval :	ULus CE	
9."★" is the key quality control point		

GT212R - 3.5 -XXP - X X - 00

①	②	③	④	⑤	⑥
① Series NO.	② Pitch	③ Poles	④ 1 Single Pitch 2 Double Pitch	⑤ Color:	⑥ Customer Request: 00--Standard
		02 02Contacts 03 03Contacts ... 24 24Contacts		1 Grey 2 Blue 3 Black 4 Green 5 Orange 6 Red 7 Transparent 8 Yellow 9 White	

4	SHRAPNEL	XXXXXX	P	STAINLESS STEEL	
3	BUTTON	XXXXXX	P	PA4T	UL94V-0
2	CONTACTS	XXXXXX	P	COPPER ALLOY	Tin Plated
1	HOUSING	XXXXXX	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	CXL	DATE	20.05.11	SIZE	A4 UNITS mm SHEET/OF 1 / 1
CHK.	DATE			SCALE	1:1
APP.	DATE			NAME	GT212R-3.50-XXP-XX-00
				DWGNO.	XXXX